

THE COMPACT AND SECURE MULTIFUNCTION A4 PRINTER YOU CAN RELY ON FOR SHORT PRINT RUNS AND AD HOC SCANNING.

i-SENSYS MF270 II series is ideal for smaller offices and workspaces that demand efficiency.

i-SENSYS MF270 II Series



EFFICIENT AND RELIABLE

Keep your workflow moving whether you're handling receipts, contracts or everyday office documents, with fast, reliable and effortless performance that helps you stay productive from the moment your day begins.

ROBUST SECURITY

Secure your documents, devices and network with robust 360-degree security and machine learning AI recommended security settings.

IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by opting for devices made with more recycled plastic.

COMPACT DESIGN

Its compact footprint makes it an ideal choice for small offices or limited workspaces where efficiency and space-saving performance matter.

SMOOTH USER EXPERIENCE

Enjoy an intuitive user experience with Master Setup, automatically downloading all required drivers and software for a smooth, hassle-free start.

TECHNICAL SPECIFICATIONS

i-SENSYS MF270 II Series

GENERAL SPECIFICATIONS	
Machine Type	Mono Laser All-In-One
Available Functions	Print, Copy, Scan and Fax
PRINT SPECIFICATIONS	
Print Speed	Single sided: Up to 29 ppm (A4) Double sided: Up to 18.5 ipm (A4)
Printing Method	Monochrome laser beam printing
Print Resolution	Up to 2400 equivalent x 600 dpi
Warm-up time	Approx. 9.0 seconds or less from power on
First-Print-Out Time	Approx: 5.4 seconds or less (400dpi) Approx: 7.1 seconds or less (600dpi)
Printer Languages	UFR II
Print Margins	5 mm-top, bottom, left and right
Toner Saver Mode	Yes
Advanced Printing Features	iOS: AirPrint, Canon PRINT app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT app Microsoft Universal Print support
COPY SPECIFICATIONS	
Copy Speed	Single sided: Up to 29 ppm (A4) Double sided: Up to 18.5 ipm (A4)
First-Copy-Out Time	MF272dw II: 7.6 seconds or less MF275dw II: ADF (A4): 8.3 seconds or less Platen (A4): 7.6 seconds or less
Copy Resolution	Up to 600 x 600 dpi
Copy Modes	Text/Photo, Text/Photo (High speed), Photo, Text
Double Sided Copying	1-sided to 2-sided (Automatic)
Multiple Copies	Up to 999 copies
Reduction / Enlargement	25-400% in 1% increments
Other Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, Job Build, N on 1, Sharpness, Erase Frame, ID card copy, Passport copy
SCAN SPECIFICATIONS	
Colour Scanning Depth	24 bit/24 bit (input/output)
Maximum Scan Width	216mm
Scan to Cloud	JPEG/PDF ¹
Compatibility	TWAIN, WIA
Greyscales	256 levels
Scan to PC	JPEG (single page only)
Scan Resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi

Scan Speed	MF272dw II: Platen: Single sided mono: 3.6 sec/page Single sided colour: 3.6 sec/page MF275dw II: Platen: Single sided mono: 3.6 sec/page Single sided colour: 3.6 sec/page ADF: Single sided mono: 24ipm (300x600dpi) Single sided colour: 24ipm (300x300dpi)
FAX SPECIFICATIONS (MF275dw II ONLY)	
Double Sided Faxing	Yes (Transmit and Receive)
Fax Memory	Up to 256 pages ²
Other Features	Sender's Name (TTI), Direct Send, TX Report, Sequential Broadcasting
Receive Mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual
Fax Resolution	Normal: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi
Group Dials/ Destinations	Max. 50 destinations in one group
Memory Backup	Permanent fax memory backup (Backup with flash memory)
Modem Speed	33.6 Kbps (Up to 3 seconds/page) ²
Sequential Broadcast	Max. 114 destinations
Speed Dials	Up to 104 dials
MEDIA HANDLING	
Scanner Type	MF272dw II: Flatbed MF275dw II: Flatbed and Automatic Document Feeder (ADF)
Paper Input (Standard)	MF272dw II: 150-sheet cassette MF275dw II: 150-sheet cassette 35-sheet ADF
Paper Output	50-sheet
Media Types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Bond paper, Label, Post card, Envelope
Media Sizes	MF272dw II: Cassette : A4, A5, A5 (Landscape), B5, A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Envelop (COM10, Monarch, DL, C5), Custom sizes: Min. 76.0 x 127 mm Max. 216.0 x 356.0 mm MF275dw II: Cassette : A4, A5, B5, A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Envelop (COM10, Monarch, DL, C5), Custom sizes: Min. 76.0 x 127 mm Max. 216.0 x 356.0 mm ADF: A4, A5, A6*, B5, Legal, Letter, Custom sizes: Min. 105 x 148 mm Max 216 x 356 mm *Attachement required

TECHNICAL SPECIFICATIONS

i-SENSYS MF270 II Series

Media Weights	MF272dw II: Cassette: 60 to 163 g/m ² MF275dw II: Cassette: 60 to 163 g/m ² ADF: 105 to 128 g/m ² (Single sheet) 50 to 105 g/m ² (Multiple sheet)
----------------------	--

Double Sided Printing	Automatic A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, Foolscap Custom size - Min. 210 x 279 mm Max. 216 x 356 mm 60 to 105 g/m ²
------------------------------	---

INTERFACE & SOFTWARE

Interface Type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection
-----------------------	---

Operating System Compatibility	Windows® 11 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 11.7 & up Linux ³
---------------------------------------	---

Network Protocol	Print: TCP/IP (LPD/Port9100/IPPS/PPS/WSD) Pull Scan: TCP/IP, USB Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): IEEE802.1x Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES)
-------------------------	--

GENERAL FEATURES

Recommended Monthly Print Volume	150 - 2,000 pages per month
Duty Cycle	Max. 20,000 pages per month ⁴
Processor Speed	1200MHz
Memory	256MB
Control Panel	MF272dw II : 5 lines B&W LCD MF275dw II : 5 lines B&W LCD
Dimensions with Trays (W x D x H)	MF272dw II: 399 mm x 374 mm x 299 mm MF275dw II: 399 mm x 374 mm x 346 mm
Installation Space (W x D x H)	MF272dw II: 399 mm x 598 mm x 607 mm MF275dw II: 459 mm x 659 mm x 618 mm
Weight	MF272dw II: Approx. 9.9 Kg MF275dw II: Approx. 11.6 Kg
Operating Environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)

Power Consumption	Maximum: Approx. 1,130 W Active printing: Approx. 409 W Standby: Approx. 4.9 W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.23 kWh/week (230V) ⁷ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
--------------------------	---

Noise Levels	Sound Pressure: Active: Simplex 51 dB Duplex 50 dB Standby: Inaudible ⁶ Sound Power ⁵ : Active: 69.3 dB or less Standby: N/A
---------------------	--

CONSUMABLES

Cartridges	Cartridge 071 (1,200 pages ⁸) ⁹ Cartridge 071H (2,500 pages ⁸) ⁹
-------------------	---

Notes:

- [1] Scan by MF Scan Utility or Canon PRINT
- [2] Based on ITU-T Standard Chart No. 1
- [3] Linux support both printing and scanning
- [4] Duty cycle is defined as the maximum number of printed pages for a single peak month.
Any usage above the recommended duty cycle may decrease the life of the product
- [5] BDeclared noise emission in accordance with ISO 7779.
- [6] Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
- [7] As per US ENERGY STAR® version3.2.
- [8] Based on ISO/IEC 19752
- [9] Printer ships with Starter Cartridge (700 pages)

i-SENSYS MF270 II Series



Canon Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V. 2026